



BRAVO 21 Zone Start Specifications (Model 21-503)

Updated: 06.01.11

| | |
|----------------------------------|--|
| Engine | Honda GXV 160 |
| Transmission | Heavy duty 2-speed gear drive transmission |
| Ground Speed | 3.0-4.2mph @ 3,200 engine rpm |
| Wheel Ratchet System | Integrated within transmission |
| Transmission Drive | 3L Kevlar Belt |
| Cutting Width | 21" |
| Deck Material | 14-gauge stamped steel with rolled under lip |
| Wear Strips | Replaceable hardened steel strips on both trim sides of mower |
| Cutting Heights | 1"-3.5" |
| Mowing Height Adjustments | 6 |
| Wheels | Radial shaped 9" semi-pneumatic wheel. Fully interchangeable front and back. Ball bearings in front, and fixed to transmission axle in rear. |
| Front Axle | 30mm steel tube |
| Bag Capacity | 2.5 Bushels |
| Mulch Plug | Standard |
| Blades | Standard: Regular lift Optional: High lift |
| Lower Handle | 34mm aircraft quality aluminum tube with no bolts, brackets or cables on the outside for a snag free smooth exterior |
| Upper Handle | 30mm aircraft quality aluminum tube shaped to fit operators hands, and narrowed to make turning easier |
| Cable Protection | Cables are routed within handle tubes for added protection |
| Blade Control | Zone Start System |
| Dry Weight | 104lbs |
| Commercial Warranty | 2 years engine, 1 year all other components |
| Suggested Retail Price | \$1099. |