



BRAVO 21 Zone Start Specifications (Model 21-503)

Updated: 06.26.2014

Engine	Honda GXV 160
Transmission	Heavy duty 2-speed gear drive transmission
Ground Speed	3.0-4.2mph @ 3,200 engine rpm
Wheel Ratchet System	Integrated within transmission
Transmission Drive	3L Kevlar Belt
Cutting Width	21"
Deck Material	14-gauge stamped steel with rolled under lip
Wear Strips	Replaceable hardened steel strips on both trim sides of mower
Cutting Heights	1"-3.5"
Mowing Height Adjustments	6
Wheels	Radial shaped 9" semi-pneumatic wheel. Fully interchangeable front and back. Ball bearings in front, and fixed to transmission axle in rear.
Front Axle	30mm steel tube
Bag Capacity	2.5 Bushels
Mulch Plug	Standard
Blades	Standard: Regular lift Optional: High lift
Lower Handle	34mm aircraft quality aluminum tube with no bolts, brackets or cables on the outside for a snag free smooth exterior
Upper Handle	30mm aircraft quality aluminum tube shaped to fit operators hands, and narrowed to make turning easier
Cable Protection	Cables are routed within handle tubes for added protection
Blade Control	Zone Start System
Dry Weight	104lbs
Commercial Warranty	2 years engine, 1 year all other components