



## BRAVO 25 Specifications (Model 25-101)

Updated: 06.26.2014

<b>Engine</b>	Honda GXV 160
<b>Transmission</b>	Heavy duty 2-speed gear drive transmission
<b>Ground Speed</b>	3.0-4.2mph @ 3,500 engine rpm
<b>Wheel Ratchet System</b>	Integrated within transmission
<b>Transmission Drive</b>	3L Kevlar Belt
<b>Cutting Deck Width</b>	25"
<b>Deck Material</b>	14-gauge stamped steel with rolled under lip
<b>Blade Drive Spindle</b>	Forged spindle shaft with die cast aluminum housing and permanently lubricated ball bearings
<b>Wear Strips</b>	Replaceable hardened steel strips on both trim sides of mower
<b>Cutting Heights</b>	1"-3.5"
<b>Mowing Height Adjustments</b>	6
<b>Wheels</b>	Radial shaped 9" semi-pneumatic wheel. Fully interchangeable front and back. Ball bearings in front and fixed to transmission axle in rear.
<b>Front Axle</b>	30mm steel tube
<b>Bag Capacity</b>	2.8 Bushels
<b>Mulch Plug</b>	Standard
<b>Blade</b>	High lift blade for excellent bagging and quality of cut
<b>Lower Handle</b>	34mm aircraft quality aluminum tube with no bolts, brackets or cables on the outside for a snag free smooth exterior
<b>Upper Handle</b>	30mm aircraft quality aluminum tube shaped to fit operators hands and narrowed to make turning easier
<b>Cable Protection</b>	Cables are routed within handle tubes for added protection
<b>Blade Control</b>	BBC
<b>Dry Weight</b>	117lbs
<b>Commercial Warranty</b>	2 years engine, 1 year all other components