



# BRAVO 21

## **BRAVO 21 ZONE START SPECIFICATIONS (Model 21-610)**

<b>ENGINE</b>	Kawasaki FJ180V
<b>TRANSMISSION</b>	Heavy duty 2-speed gear drive transmission
<b>GROUND SPEED</b>	2.8 - 3.9 mph @ 3,300 engine rpm**
<b>WHEEL RATCHET SYSTEM</b>	Integrated within transmission
<b>TRANSMISSION DRIVE</b>	3L Kevlar Belt
<b>CUTTING DECK WIDTH</b>	21"
<b>DECK MATERIAL</b>	14-gauge stamped steel with rolled under lip
<b>WEAR STRIPS</b>	Replaceable hardened steel strips on both trim sides of mower
<b>CUTTING HEIGHTS</b>	1" - 4.5" in .5" increments
<b>MOWING HEIGHT ADJUSTMENTS</b>	8
<b>WHEELS</b>	Radial shaped 9" wheels. Fully interchangeable front and back. Ball bearings in front and fixed to transmission axle in rear.
<b>FRONT AXLE</b>	30 mm steel tube
<b>BAG CAPACITY</b>	2.5 Bushels
<b>MULCH PLUG</b>	Standard
<b>BLADE</b>	Standard: Regular Lift / Optional: High Lift
<b>LOWER HANDLE</b>	34 mm aircraft quality aluminum tube with no bolts, brackets or cables on the outside for a snag free smooth exterior
<b>UPPER HANDLE</b>	Narrowed upper handle design for easier turning. Control balls fitted to handle for operator comfort.
<b>CABLE PROTECTION</b>	Cables are routed within handle tubes for added protection
<b>BLADE CONTROL</b>	Zone Start System
<b>DRY WEIGHT</b>	117 lbs
<b>COMMERCIAL WARRANTY</b>	3 Year Engine / 2 Year Limited Warranty

\*Specifications are subject to change without notice. \*\*Ground speeds are approximate measurements.